

## 株式会社アペックス

## [2016年度 グリーン購入法適合機種一覧]

## 缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
T-CVA-0930SWHP	965kWh	106%	R744	1	320g
T-CVA-0936WHP	988kWh	110%	R744	1	320g
CVA3009UNH	965kWh	101%	R744	1	320g
CVA4209DNH	1468kWh	100%	R744	1	430g
T-CVA-1130SWHP	870kWh	117%	R744	1	290g
T-CVA-1136WHP	850kWh	128%	R744	1	290g
FAG30S6LT7PS	980kWh	114%	R744	1	380g
OU-FJ36M6RD8P	990kWh	110%	R744	1	420g
OU-FJ30M6RD8P	980kWh	104%	R744	1	420g
OU-FJ36M6RD9P	1080kWh	100%	R744	1	450g
OU-FJ36M6RDXP	1080kWh	100%	R744	1	450g
FV30M5RD1PS	880kWh	114%	R744	1	360g
FV36M6RD1PS	960kWh	114%	R744	1	360g
OU-FV36M6RD1PS	960kWh	114%	R744	1	360g
FV30M6RD1PS	975kWh	106%	R744	1	360g
OU-FV30M6RD1PS	975kWh	106%	R744	1	360g
OU-FV30M5RD1PS	880kWh	114%	R744	1	360g
F-AP1136S6HPCA	1025kWh	107%	R744	1	360g
NS-AP0730S5HP	960kWh	105%	R600a	3	100g
N-AP0825S5HP	950kWh	101%	R600a	3	100g
N-AP0830S5HP	960kWh	105%	R600a	3	100g
N-AP0830S6HP	970kWh	112%	R600a	3	100g
N-AP0836S6HP	990kWh	116%	R600a	3	100g
N-0830S6UDHP	970kWh	112%	R600a	3	100g
N-0836S6UDHP	990kWh	116%	R600a	3	100g
N-AP0925S5HP	950kWh	101%	R600a	3	97g
N-AP0930S5HP	960kWh	105%	R600a	3	97g
N-AP0930S6HP	970kWh	112%	R600a	3	97g
N-AP0936S6HP	990kWh	116%	R600a	3	97g
N-AP0942S6HP	1080kWh	113%	R600a	3	97g
N-0930S6UDHP	970kWh	112%	R600a	3	97g
N-0936S6UDHP	990kWh	116%	R600a	3	97g
N-0942S6UDHP	1080kWh	113%	R600a	3	97g
N-AP1025S5HP	940kWh	102%	R600a	3	96g
N-AP1030S5HP	950kWh	106%	R600a	3	96g
N-AP1030S6HP	960kWh	113%	R600a	3	96g
N-AP1036S6HP	970kWh	118%	R600a	3	96g
N-AP1042S6HP	980kWh	124%	R600a	3	96g
N-1030S6UDHP	960kWh	113%	R600a	3	96g
N-1036S6UDHP	970kWh	118%	R600a	3	96g
N-1042S6UDHP	970kWh	124%	R600a	3	96g
N-AP1120S5HP	794kWh	100%	R600a	3	42g/46g
N-AP1125S5HP	833kWh	115%	R600a	3	46g/50g
N-AP1130S5HP	864kWh	117%	R600a	3	46g/50g
N-AP1130S6HP	858kWh	126%	R600a	3	46g/50g
N-AP1136S6HP	940kWh	130%	R600a	3	46g/50g
N-AP1142S6HP	849kWh	144%	R600a	3	47g/50g
N-AP1130S6UH	858kWh	126%	R600a	3	46g/50g
N-AP1136S6UH	940kWh	130%	R600a	3	46g/50g
N-AP1142S6UH	849kWh	144%	R600a	3	47g/50g

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
N-AP1220S5HP	789kWh	101%	R600a	3	50g
N-AP1225S5HP	828kWh	115%	R600a	3	50g
N-AP1230S5HP	852kWh	119%	R600a	3	50g
N-AP1230S6HP	853kWh	127%	R600a	3	50g
N-AP1236S6HP	872kWh	132%	R600a	3	50g
N-AP1242S6HP	835kWh	146%	R600a	3	47/50g
N-AP1230S6UH	853kWh	127%	R600a	3	50g
N-AP1236S6UH	872kWh	132%	R600a	3	50g
N-AP1242S6UH	835kWh	146%	R600a	3	47/50g
N-AP12303PHP	852kWh	133%	R600a	3	50g
F-AP1236S6W	850KWh	129%	R1234yf	4	240g
N-AP1320S5HP	789kWh	101%	R600a	3	50g
N-AP1325S5HP	803KWh	120%	R600a	3	50g
N-AP1330S5HP	827KWh	123%	R600a	3	50g
N-AP13303PHP	827KWh	137%	R600a	3	50g
N-AP1342S6HP	835kWh	147%	R600a	3	50g
N-AP1330S6MP	710kWh	153%	R600a	3	50g
N-AP1336S6MP	730kWh	158%	R600a	3	50g
N-AP1330S6UH	828kWh	131%	R600a	3	50g
N-AP1336S6UH	847kWh	136%	R600a	3	50g
N-AP1342S6UH	835kWh	147%	R600a	3	50g
F-AP1330WA	765kWh	135%	R1234yf	4	240g
F-AP1336WA	790kWh	138%	R1234yf	4	240g
T-CVA-1330SWHP	815kWh	125%	R744	1	240g
T-CVA-1336WHP	820kWh	132%	R744	1	240g
N-AP1420S5HP	779kWh	102%	R600a	3	50g
N-AP1425S5HP	782kWh	122%	R600a	3	50g
N-AP1430S5HP	789kWh	128%	R600a	3	50g
N-AP1430S6MP	617kWh	176%	R600a	3	50g
N-AP14303PHP	789kWh	141%	R600a	3	50g
N-AP1436S6MP	634kWh	182%	R600a	3	50g
N-AP14353PHP	927kWh	136%	R600a	3	50g
N-AP1442S6HP	858kWh	142%	R600a	3	50g
N-AP1436S6UH	849kWh	135%	R600a	3	50g
F-AP1430S6WA	600kwh	172%	R1234yf	4	240g
F-AP14303PWA	600kwh	180%	R1234yf	4	240g
F-AP1436S6WA	615kwh	178%	R1234yf	4	240g
F-AP1442S6WA	700kWh	172%	R1234yf	4	250g
T-CVA-1430SWHP	580kwh	179%	R744	1	200g
			HFO1234yf	4	200g
T-CVA-1436WHP	595kwh	184%	R744	1	200g
			HFO1234yf	4	200g
F-AP1536S6WA	580kWh	190%	R1234yf	4	240g
F-AP1530S6WA	565kWh	184%	R1234yf	4	240g
F-AP1530P3WA	575kWh	189%	R1234yf	4	240g
F-AP1542S6WA	680kWh	171%	R1234yf	4	250g
T-CVA-1530SWHP	640kwh	162%	R744	1	150g
			HFO1234yf	4	100g
T-CVA-1536WHP	645kwh	171%	R744	1	150g
			HFO1234yf	4	100g
N-AP1530S5HP	784kWh	129%	R600a	3	53g
N-AP1530S6MP	607kWh	179%	R600a	3	53g
N-AP15303PHP	784kWh	142%	R600a	3	53g
N-AP1536S6MP	629kWh	183%	R600a	3	53g
N-AP1520S5HP	779kWh	102%	R600a	3	53g
N-AP1525S5HP	777kWh	123%	R600a	3	53g

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
N-AP1542S6HP	858kWh	142%	R600a	3	53g
N-AP1536S6UH	844kWh	136%	R600a	3	53g
N-AP15353PHP	807kWh	156%	R600a	3	53g
N-AP1642S6HP	858kWh	142%	R600a	3	53g
N-AP16353PHP	807kWh	156%	R600a	3	53g
N-AP1630S5HP	784kWh	129%	R600a	3	53g
N-AP1625S5HP	777kWh	123%	R600a	3	53g
N-AP1620S5HP	779kWh	102%	R600a	3	50g
N-AP1636S6MP	629kWh	183%	R600a	3	53g
N-AP1630S6MP	607kWh	179%	R600a	3	53g
F-AP1636S6WA	580kWh	190%	R1234yf	4	240g
F-AP1630S6WA	565kWh	184%	R1234yf	4	240g

#### カップ機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
APEX120QREC-G	2584kWh	102%	R134a(HFC)	1300	290g
APEX120QRECU-G	2584kWh	102%	R134a(HFC)	1300	290g
APEX120QVR II -C	2362kWh	106%	R134a(HFC)	1300	270g
APEX100QRC-G	1582kWh	110%	R134a(HFC)	1300	210g
APEX100QR CN-G	1582kWh	110%	R134a(HFC)	1300	210g
APEX100QR CU-G	1582kWh	110%	R134a(HFC)	1300	210g
APEX100QR F-G	1482kWh	118%	R134a(HFC)	1300	210g
APEX85QVR	886kWh	125.9%	R744(CO2)	1	180g
APEX120QREC-GC	2584kWh	102%	R1234yf	4	147g
APEX120QRECU-GC	2584kWh	102%	R1234yf	4	147g
APEX120QRECH-GC	2311kWh	114%	R1234yf	4	147g
APEX120QRECN-GC	2311kWh	114%	R1234yf	4	147g
APEX100QRFB-G	1482kWh	118%	R134a(HFC)	1300	210g
APEX-100RS	1436kWh	141%	R1234yf	4	147g