

大塚ウエルネスベンディング株式会社

[2020年度 グリーン購入法適合機種一覧]

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
F-SQ2P2024-HPE	620	128%	R1234yf	1	200
F-SQ2P3036-HPE	565	178%	R1234yf	1	240
F-SQ2P3030-HPE	565	183%	R1234yf	1	240
F-SQ2P3636-HPE	580	190%	R1234yf	1	240
F-SQ3P3036-HPE	575	186%	R1234yf	1	240
F-SQ3P3636-HPE	660	172%	R1234yf	1	240
F-SQ4P3036-HPE	699	168%	R1234yf	1	240
F-SQ2P1624U-HP	790	124%	R1234yf	1	190
F-SQ2P2436U-HPE	680	185%	R1234yf	1	210
NS-SQ2P2530-HPE	582	164%	R600a	3	53
NS-SQ2P3030-HPE	607	179%	R600a	3	53
NS-SQ3P2430-HP	820	114%	R600a	3	50
NS-SQ3P3036-HPE	589	190%	R600a	3	53
NS-SQ4P2020-NF	1391	78%	R600a	3	50
NS-SQ2P2030HPEV	667	120%	R600a	3	50
CD-SQ1P1818-HP	735kwh	103%	R1234yf	1	120
CD-SQ2P1212-HP	760kwh	107%	R1234yf	1	130
CD-SQ2P1530U-HP	865kwh	121%	R1234yf	1	130
CD-SQ2P2030U-HP	830kwh	145%	R1234yf	1	130
CD-SQ2P2424-HP	830kwh	102%	R1234yf	1	130
CD-SQ4P2430-HP	865kwh	112%	R1234yf	1	150
CD-SQ4P3536-HP	940kwh	141%	R1234yf	1	160
CD-SQ4P4242-HP	990kwh	131%	R1234yf	1	160
NS-19WP2030E	667kWh	120%	R600a	3	50g
NS-19WP2530E	582kWh	164%	R600a	3	53g
NS-19WP3036E	589kWh	172%	R600a	3	53g
NS-19WP3030E	607kWh	179%	R600a	3	53g
NS-19WP3636E	629kWh	183%	R600a	3	53g
NS-19TP2430HP	820kWh	114%	R600a	3	50g
NS-19TP3030E	589kWh	190%	R600a	3	53g
NS-19TP3536HP	807kWh	156%	R600a	3	53g
NS-19FP3036E	629kWh	155%	R600a	3	50g
CD-19WP1212-HP	760 kwh	107%	R1234yf	1	130g
CD-19WP1530U-HP	865 kwh	121%	R1234yf	1	130g
CD-19P1818-HP	735 kwh	103%	R1234yf	1	120g
CD-19WP2424-HP	830kwh	102%	R1234yf	1	130g
CD-19WP3030-HPE	600kwh	174%	R1234yf	1	150g
CD-19WP3036-HPE	585kwh	171%	R1234yf	1	150g
CD-19WP3636-HPE	605kwh	183%	R1234yf	1	150g
CD-19TP3036-HP	725kwh	150%	R1234yf	1	150g
CD-19TP3642-HP	760kwh	151%	R1234yf	1	160g
CD-19TP4242-HP	925kwh	139%	R1234yf	1	160g
F-19WP2024-HPE	620kWh	128%	R1234yf	1	200g
F-19WP2530-HPE	540kWh	177%	R1234yf	1	210g
F-19WP3036-HPE	565kWh	178%	R1234yf	1	210g
F-19WP3030-HPE	565kWh	184%	R1234yf	1	210g
F-19TP3636-HPE	575kWh	189%	R1234yf	1	210g
F-19WP3636-HPE	580kWh	190%	R1234yf	1	210g
F-19WP1624U-HP	790kWh	124%	R1234yf	1	190g
F-19WP2030U-HPE	670kWh	178%	R1234yf	1	210g

## 缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
F-19TP2430-HP	795kWh	109%	R1234yf	1	190g
F-19TP3636-HPE	660kWh	172%	R1234yf	1	240g
F-19FP3036-HPE	699kWh	155%	R1234yf	1	240g
NS-18WP2030HPJEL	667kWh	120%	R600a	3	50g
NS-18TP2430-HP	820kWh	114%	R600a	3	50g
NS-18TP3036-HPE	589kWh	190%	R600a	3	53g
NS-18TP3536-HP	807kWh	156%	R600a	3	53g
NS-18WP2030-HPE	667kWh	120%	R600a	3	50g
NS-18WP2530-HPE	582kWh	164%	R600a	3	53g
NS-18WP3030-HPE	607kWh	179%	R600a	3	53g
NS-18WP3036-HPE	589kWh	172%	R600a	3	53g
NS-18WP3636-HPE	629kWh	183%	R600a	3	53g
CD-18P1818-HP	735kWh	104%	R1234yf	1	120g
CD-18TP3036-HP	725kWh	150%	R1234yf	1	150g
CD-18TP4242-HP	925kWh	139%	R1234yf	1	160g
CD-18WP1212-HP	760kWh	107%	R744	1	190g
CD-18WP1530U-HP	865kWh	120%	R744	1	160g
CD-18WP2030U-HP	830kWh	144%	R744	1	160g
CD-18WP2424-HP	830kWh	103%	R744	1	150g
CD-18WP2530-HPE	580kWh	163%	R1234yf	1	150g
CD-18WP3030-HPE	600kWh	174%	R1234yf	1	150g
CD-18WP3036-HPE	585kWh	171%	R1234yf	1	150g
F-18WP2024-HPE	620kWh	128%	R1234yf	1	200g
F-18WP2530-HPE	540kWh	177%	R1234yf	1	210g
F-18WP3036-HPE	565kWh	178%	R1234yf	1	210g
F-18WP3030-HPE	565kWh	184%	R1234yf	1	210g
F-18TP3636-HPE	575kWh	189%	R1234yf	1	210g
F-18WP3636-HPE	580kWh	190%	R1234yf	1	210g
F-18WP1624U-HP	790kWh	124%	R1234yf	1	190g
NS-17WP2030HPJEL	667kWh	120%	R600a	3	50g
NS-17TP2430-HP	820kWh	114%	R600a	3	50g
NS-17TP3036-HPE	589kWh	190%	R600a	3	53g
NS-17TP3536-HP	807kWh	156%	R600a	3	53g
NS-17WP1530U-HP	916kWh	113%	R600a	3	45g
NS-17WP2030-HPE	667kWh	120%	R600a	3	50g
NS-17WP2530-HPE	582kWh	164%	R600a	3	53g
NS-17WP3030-HPE	607kWh	179%	R600a	3	53g
NS-17WP3036-HPE	589kWh	172%	R600a	3	53g
NS-17WP3636-HPE	629kWh	183%	R600a	3	53g
CD-17WP3030-HP	805kWh	129%	R744	1	160g
CD-17WP3636-HP	820kWh	134%	R744	1	160g
CD-17P1818-HP	735kWh	103%	R744	1	170g
CD-17TP3036-HP	755kWh	144%	R744	1	160g
CD-17TP4242-HP	925kWh	139%	R744	1	170g
CD-17WP1212-HP	760kWh	107%	R744	1	190g
CD-17WP2030U-HP	830kWh	143%	R744	1	160g
F-17WP2024-HPE	620kWh	128%	R1234yf	1	200g
F-17WP2530-HPE	540kWh	177%	R1234yf	1	210g
F-17WP3036-HPE	565kWh	178%	R1234yf	1	210g
F-17WP3030-HPE	565kWh	184%	R1234yf	1	210g
F-17TP3636-HPE	575kWh	189%	R1234yf	1	210g
F-17WP3636-HPE	580kWh	190%	R1234yf	1	210g
NS-16WP2030-HPE	667kWh	120%	R600a	3	50g
NS-16WP2530-HPE	582kWh	164%	R600a	3	53g
NS-16WP3036-HPE	589kWh	172%	R600a	3	53g

## 缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
NS-16WP1530U-HP	916kWh	113%	R600a	3	45g
NS-16TP2430-HP	820kWh	114%	R600a	3	50g
NS-16TP3036-HPE	589kWh	190%	R600a	3	53g
NS-16TP2536-HP	784kWh	125%	R600a	3	53g
CD-16WP1212-HP	760kWh	107%	R744	1	190g
CD-16P1818-HP	735kWh	103%	R744	1	170g
CD-16WP2030U-HP	830kWh	144%	R744	1	160g
CD-16WP3030-HP	805kWh	129%	R744	1	160g
CD-16WP3636-HP	820kWh	134%	R744	1	160g
CD-16TP4242-HP	925kWh	139%	R744	1	170g
F-16WP2024-HPE	620kWh	128%	R1234yf	1	200g
F-16WP2530-HPE	540kWh	177%	R1234yf	1	240g
F-16WP3036-HPE	565kWh	178%	R1234yf	1	240g
F-16WP3030-HPE	565kWh	184%	R1234yf	1	240g
F-16WP3636-HPE	580kWh	190%	R1234yf	1	240g
NS-15TP2430-HP	820kWh	114%	R600a	3	53g
NS-15TP3036-HPE	589kWh	190%	R600a	3	53g
NS-15WP1530U-HP	916kWh	113%	R600a	3	45g
NS-15WP2030-HPE	667kWh	120%	R600a	3	53g
NS-15WP2030U-HP	827kWh	145%	R600a	3	53g
NS-15WP2530-HPE	582kWh	164%	R600a	3	53g
NS-15WP3030-HPE	607kWh	179%	R600a	3	53g
NS-15WP3036-HPE	589kWh	172%	R600a	3	53g
NS-15WP3636-HPE	629kWh	183%	R600a	3	53g
CD-15WP1212-HP	780kWh	101%	R744	1	180g
CD-15P1818-HP	745kWh	102%	R744	1	200g
CD-15WP2030U-HP	825kWh	141%	R744	1	220g
CD-15WP2530-HPE	620kWh	153%	R744/1234yf	1	150g/100g
CD-15WP3030-HPE	640kWh	163%	R744/1234yf	1	150g/100g
CD-15WP3036-HPE	625kWh	160%	R744/1234yf	1	150g/100g
CD-15TP3036-HPE	605kWh	180%	R744/1234yf	1	150g/100g
CD-15WP3636-HPE	645kWh	171%	R744/1234yf	1	150g/100g
CD-15TP4242-HPE	925kWh	139%	R744/1234yf	1	160g/100g
F-15WP2530-HPE	540kWh	177%	R1234yf	1	240g
F-15WP3036-HPE	565kWh	178%	R1234yf	1	240g
F-15WP3030-HPE	565kWh	184%	R1234yf	1	240g
F-15WP3636-HPE	580kWh	190%	R1234yf	1	240g
F-15WP1624U-HP	790kWh	124%	R1234yf	1	190g
F-15TP3036-HPE	575kWh	189%	R1234yf	1	240g
NS-14TP2430-HP	820kWh	114%	R600a	3	50g
NS-14WP1530U-HP	1012kWh	107%	R600a	3	45g
NS-14WP2030-HP	779kWh	102%	R600a	3	50g
NS-14WP2530-HPE	582kWh	165%	R600a	3	50g
NS-14WP3030-HPE	617kWh	176%	R600a	3	50g
NS-14WP3036-HPE	589kWh	172%	R600a	3	50g
NS-14WP3636-HPE	634kWh	182%	R600a	3	50g
CD-14P1818-HP	745kWh	101%	R744	1	200g
CD-14TP4242-HP	975kWh	130%	R744	1	240g
CD-14WP2530-HPE	560kWh	168%	R744/R1234yf	1	200g/200g
CD-14WP3030-HPE	580kWh	179%	R744/R1234yf	1	200g/200g
CD-14WP1212-HP	780kWh	101%	R744	1	180g
CD-14WP2030U-HP	825kWh	140%	R744	1	220g
F-14WP1624U-HP	790kWh	124%	R1234yf	1	190g
F-14WP2530-HPE	590kWh	160%	R1234yf	1	240g
F-14WP3036-HPE	595kWh	168%	R1234yf	1	240g

## 缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
F-14WP3030-HPE	600kWh	172%	R1234yf	1	240g
F-14WP3636-HPE	615kWh	178%	R1234yf	1	240g
F-14TP3036-HPE	600kWh	180%	R1234yf	1	240g
NS-13WP2030-HP	801kWh	100%	R600a	3	50g
NS-13WP2530-HPE	737kWh	130%	R600a	3	50g
NS-13WP3036-HPE	764kWh	132%	R600a	3	50g
CD-13P1818-HP	755kWh	100%	R744	1	200g
CD-13TP4242-HP	1005kWh	126%	R744	1	240g
CD-13WP2530-HPE	800kWh	116%	R744	1	240g
CD-13WP3036-HPE	805kWh	122%	R744	1	240g
CD-13WP1530U-HP	885kWh	115%	R744	1	230g
CD-13WP3030-HPE	815kWh	125%	R744	1	240g
CD-13WP3636-HPE	820kWh	132%	R744	1	240g
CD-13WP1212-HP	785kWh	100%	R744	1	180g
CD-13WP2030U-HP	840kWh	138%	R744	1	220g
CD-13TP3036-HP	795kWh	135%	R744	1	240g
F-13WP2530-HPE	735kWh	129%	R1234yf	1	240g
F-13WP3030-HPE	765kWh	135%	R1234yf	1	240g
F-13WP3036-HPE	770kWh	130%	R1234yf	1	240g
F-13WP3636-HPE	790kWh	138%	R1234yf	1	220g
F-13WP1624U-HP	915kWh	107%	R1234yf	1	190g
NS-12WP1530U-HP	1010kWh	102%	R600a	3	45g
NS-12WP2030-HP	794kWh	100%	R600a	3	50g
NS-12WP2530-HP	833kWh	115%	R600a	3	50g
NS-12WP3036-HP	864kWh	117%	R600a	3	50g
CD-12WP1212-HPC	785kWh	100%	R744	1	180g
CD-12P1818-HPC	755kWh	100%	R744	1	200g
CD-12WP2030UHPC	830kWh	140%	R744	1	220g
CD-12WP2530-HPC	830kWh	112%	R744	1	240g
CD-12WP3030-HPC	850kWh	120%	R744	1	240g
CD-12WP3636-HPC	850kWh	128%	R744	1	240g
CD-12TP4242-HPC	995kWh	128%	R744	1	240g
F-12WP2530-HP	795kWh	119%	R1234yf	1	240g
F-12WP3030-HP	820kWh	126%	R1234yf	1	240g
F-12WP3036-HP	830kWh	120%	R1234yf	1	240g
F-12TP3036-HP	910kWh	119%	R1234yf	1	220g
NS-11WP2030-HP	794kWh	100%	R600a	3	88g
NS-11WP2530-HP	833kWh	115%	R600a	3	88g
NS-11WP3036-HP	864kWh	117%	R600a	3	96g
NS-11TP3036UDHP	864kWh	131%	R600a	3	96g
CD-11WP3636-HPC	850kWh	128%	R744	1	290g
CD-11WP3036-HPC	835kWh	117%	R744	1	290g
CD-11TP4242-HPC	1313kWh	111%	R744	1	430g
CD-11P1818-HPC	755kWh	100%	R744	1	280g
CD-11WP2030UHPC	830kWh	140%	R744	1	280g
CD-11WP2530-HPC	855kWh	108%	R744	1	290g
CD-11WP3030-HPC	870kWh	117%	R744	1	290g
CD-10WP3036HPCH	950kWh	103%	R134a	1300	230g