

[2020年度 グリーン購入法適合機種一覧]

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BFH2025UB	565kWh	168%	1234yf	<1	240g
BFH2030SB	590kWh	176%	1234yf	<1	240g
BFH2030UB	595kWh	169%	1234yf	<1	240g
BFH2036SB	610kWh	181%	1234yf	<1	240g
BF2024TPB	820kWh	113%	1234yf	<1	190g
BFH2030TPB	605kWh	177%	1234yf	<1	240g
BFH2036TPB	690kWh	164%	1234yf	<1	240g
BFH2030QPB	729kWh	161%	1234yf	<1	240g
BFH2035QPB	810kWh	165%	1234yf	<1	240g
BFH2036QPB	880kWh	131%	1234yf	<1	240g
BFH2042QPB	985kWh	133%	1234yf	<1	240g
BF2016UB	810kWh	121%	1234yf	<1	190g
BFH2020SB	640kWh	121%	1234yf	<1	200g
BFH2024UB	710kWh	178%	1234yf	<1	210g
BFH2024SB	660kWh	130%	1234yf	<1	200g
WFH2030STB	590kWh	176%	1234yf	<1	240g
WFH2030UTB	595kWh	169%	1234yf	<1	240g
WFH2036STB	610kWh	181%	1234yf	<1	240g
WFH2030TPTB	605kWh	177%	1234yf	<1	240g
BFHT2030UB	595kWh	169%	1234yf	<1	240g
BFHT2030UBOB	595kWh	169%	1234yf	<1	240g
WF2020LHB	930kWh	134%	1234yf	<1	150g
WFH2025UB	565kWh	168%	1234yf	<1	240g
WFH2030SB	590kWh	176%	1234yf	<1	240g
WFH2030UB	595kWh	169%	1234yf	<1	240g
WFH2036SB	610kWh	181%	1234yf	<1	240g
WFH2020SB	640kWh	121%	1234yf	<1	200g
WFH2024SB	660kWh	130%	1234yf	<1	200g
WFH2042QPB	985kWh	133%	1234yf	<1	240g
BD2018TB	895kwh	123%	1234yf	<1	130g
BD2018UB	730kwh	103%	1234yf	<1	120g
BD2020UB	820kwh	143%	1234yf	<1	130g
BD2030SB	760kwh	134%	1234yf	<1	150g
BD2036SB	780kwh	138%	1234yf	<1	150g
BD2030TPB	715kwh	148%	1234yf	<1	150g
WD2030TPB	715kwh	148%	1234yf	<1	150g
BD2036TPB	750kwh	149%	1234yf	<1	160g
WD2036TPB	750kwh	149%	1234yf	<1	160g
BD2024QPB	875kwh	111%	1234yf	<1	150g
BD2030QPB	895kwh	133%	1234yf	<1	160g
BD2035QPB	950kwh	141%	1234yf	<1	160g
BD2036QPB	885kwh	131%	1234yf	<1	160g
BD2042QPB	1000kwh	130%	1234yf	<1	160g
WD2042QPB	1000kwh	130%	1234yf	<1	160g
BD2030SRWB	760kwh	134%	1234yf	<1	150g
BD2030QPRWB	895kwh	133%	1234yf	<1	160g
BD2036QPRWB	885kwh	131%	1234yf	<1	160g
BD2042QPRWB	1000kwh	130%	1234yf	<1	160g
BN2015TB	965kWh	107%	R600a	3	45g
BN2018TB	1006kWh	108%	R600a	3	45g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BN2024UB	957kWh	132%	R600a	3	53g
BNV2025UB	631kWh	152%	R600a	3	53g
BNV2030SB	656kWh	165%	R600a	3	53g
BNV2030UB	672kWh	151%	R600a	3	53g
BNV2036SB	712kWh	162%	R600a	3	53g
BN2024TPB	755kWh	124%	R600a	3	50g
BNV2025QPB	674kWh	129%	R600a	3	50g
BNV2030QPB	712kWh	137%	R600a	3	50g
WNV2025UB	631kWh	152%	R600a	3	53g
WNV2030UB	672kWh	151%	R600a	3	53g
WNV2030SB	656kWh	165%	R600a	3	53g
WNV2036SB	712kWh	162%	R600a	3	53g
WNV2030QPB	712kWh	137%	R600a	3	50g
BFH1942TPB	750kWh	161%	1234yf	<1	240g
WFH1942TPB	750kWh	161%	1234yf	<1	240g
BFH1936TPB	660kWh	172%	1234yf	<1	210g
BFH1936SB	580kWh	190%	1234yf	<1	210g
WFH1936TPB	660kWh	172%	1234yf	<1	210g
WFH1936SB	580kWh	190%	1234yf	<1	210g
WFH1936STB	580kWh	190%	1234yf	<1	210g
BFH1935TPB	700kWh	176%	1234yf	<1	240g
WFH1935TPB	700kWh	176%	1234yf	<1	240g
BFH1930TPB	575kWh	189%	1234yf	<1	210g
BFH1930QPB	699kWh	155%	1234yf	<1	240g
BFH1930SB	565kWh	184%	1234yf	<1	210g
BFH1930UB	565kWh	187%	1234yf	<1	210g
BFHT1930UB	565kWh	178%	1234yf	<1	210g
BFHT1930UBOB	635kWh	177%	1234yf	<1	240g
BFT1930SKB	995kWh	104%	1234yf	<1	220g
WFH1930TPB	575kWh	189%	1234yf	<1	210g
WFH1930UTB	565kWh	178%	1234yf	<1	210g
WFH1930STB	565kWh	184%	1234yf	<1	210g
WFH1930SB	565kWh	184%	1234yf	<1	210g
WFH1930UB	565kWh	187%	1234yf	<1	210g
WFH1930TPTB	575kWh	189%	1234yf	<1	210g
BFH1925UB	540kWh	177%	1234yf	<1	210g
WFH1925UB	540kWh	177%	1234yf	<1	210g
BF1924TPB	795kWh	117%	1234yf	<1	190g
BFH1924SB	640kWh	134%	1234yf	<1	200g
WFH1924SB	640kWh	134%	1234yf	<1	200g
WFH1920SB	620kWh	128%	1234yf	<1	200g
BFH1920SB	620kWh	128%	1234yf	<1	200g
BF1916UB	790kWh	124%	1234yf	<1	190g
BFH1842SB	750kWh	161%	1234yf	<1	240g
WFH1842SB	750kWh	161%	1234yf	<1	240g
BFH1836SB	580kWh	190%	1234yf	<1	210g
BFA1836SB	450kWh	245%	1234yf	<1	240g
BFH1836TPB	660kWh	172%	1234yf	<1	210g
WFH1836SB	580kWh	190%	1234yf	<1	210g
WFH1836STB	580kWh	190%	1234yf	<1	210g
WFH1836TPB	660kWh	172%	1234yf	<1	210g
BFH1835TPB	700kWh	176%	1234yf	<1	240g
WFH1835TPB	700kWh	176%	1234yf	<1	240g
BFH1830SB	565kWh	184%	1234yf	<1	210g
BFH1830UB	565kWh	178%	1234yf	<1	210g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BFH1830TPB	575kWh	189%	1234yf	<1	210g
WFH1830SB	565kWh	184%	1234yf	<1	210g
WFH1830STB	565kWh	184%	1234yf	<1	210g
WFH1830UB	565kWh	178%	1234yf	<1	210g
WFH1830UTB	565kWh	178%	1234yf	<1	210g
WFH1830TPB	575kWh	189%	1234yf	<1	210g
WFH1830TPTB	575kWh	189%	1234yf	<1	210g
BFHT1830UB	565kWh	178%	1234yf	<1	210g
BFHT1830UBOB	635kWh	157%	1234yf	<1	240g
BFT1830SKB	995kWh	104%	1234yf	<1	220g
BFH1825UB	540kWh	177%	1234yf	<1	210g
WFH1825UB	540kWh	177%	1234yf	<1	210g
BFH1824SB	640kWh	134%	1234yf	<1	200g
BF1824TPB	795kWh	117%	1234yf	<1	190g
BFH1824QPB	596kWh	182%	1234yf	<1	210g
WFH1824SB	640kWh	134%	1234yf	<1	200g
BFH1820SB	620kWh	128%	1234yf	<1	200g
WFH1820SB	620kWh	128%	1234yf	<1	200g
BF1816UB	790kWh	124%	1234yf	<1	190g
BFH1736SB	580kWh	190%	1234yf	<1	210g
BFH1736TPB	660kWh	172%	1234yf	<1	240g
BFA1736SB	450kWh	245%	1234yf	<1	240g
WFH1736STB	580kWh	190%	1234yf	<1	210g
BFH1730SB	565kWh	184%	1234yf	<1	210g
BFH1730UB	565kWh	178%	1234yf	<1	210g
BFH1730TPB	575kWh	189%	1234yf	<1	210g
WFH1730STB	565kWh	184%	1234yf	<1	210g
WFH1730UTB	565kWh	178%	1234yf	<1	210g
BFHT1730UB	565kWh	178%	1234yf	<1	210g
BFHT1730UBOB	635kWh	157%	1234yf	<1	240g
BFT1730SKB	995kWh	104%	1234yf	<1	220g
BFH1725UB	540kWh	177%	1234yf	<1	210g
WFH1725UTB	540kWh	177%	1234yf	<1	210g
BF1724TPB	795kWh	117%	1234yf	<1	190g
BFH1724QPB	596kWh	182%	1234yf	<1	210g
BFH1724SB	640kWh	134%	1234yf	<1	210g
BF1716UB	790kWh	124%	1234yf	<1	190g
BFH1636SB	580kWh	190%	1234yf	<1	240g
BFA1636SB	450kWh	245%	1234yf	<1	240g
WFH1636STB	580kWh	190%	1234yf	<1	240g
BFH1630SB	565kWh	184%	1234yf	<1	240g
BFH1630UB	565kWh	178%	1234yf	<1	240g
BFH1630TPB	575kWh	189%	1234yf	<1	240g
WFH1630STB	565kWh	184%	1234yf	<1	240g
WFH1630UTB	565kWh	178%	1234yf	<1	240g
BFHT1630UB	565kWh	178%	1234yf	<1	240g
BFHT1630UBOB	635kWh	157%	1234yf	<1	240g
BFT1630SKB	995kWh	104%	1234yf	<1	220g
BFH1625UB	540kWh	177%	1234yf	<1	240g
WFH1625UTB	540kWh	177%	1234yf	<1	240g
BF1624TPB	795kWh	117%	1234yf	<1	190g
BFH1624QPB	596kWh	182%	1234yf	<1	240g
BFH1624SB	640kWh	134%	1234yf	<1	200g
BFH1624UB	680kWh	185%	1234yf	<1	240g
BF1616UB	790kWh	124%	1234yf	<1	190g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BFH1536SB	580kWh	190%	1234yf	<1	240g
BFA1536SB	450kWh	245%	1234yf	<1	240g
WFH1536STB	580kWh	190%	1234yf	<1	240g
BFH1530UB	565kWh	178%	1234yf	<1	240g
WFH1530STB	565kWh	184%	1234yf	<1	240g
WFH1530UTB	565kWh	178%	1234yf	<1	240g
BFHT1530UB	565kWh	178%	1234yf	<1	240g
BFHT1530UBOB	635kWh	157%	1234yf	<1	240g
BFT1530SKB	995kWh	104%	1234yf	<1	220g
WFH1525UTB	540kWh	177%	1234yf	<1	240g
BFH1524SB	640kWh	134%	1234yf	<1	200g
BFH1524UB	680kWh	185%	1234yf	<1	240g
BF1516UB	790kWh	124%	1234yf	<1	190g
BFH1436SB	615kWh	178%	1234yf	<1	240g
WFH1436STB	615kWh	178%	1234yf	<1	240g
BFH1430SB	600kWh	172%	1234yf	<1	240g
BFH1430UB	595kWh	168%	1234yf	<1	240g
BFH1430TPB	600kWh	180%	1234yf	<1	240g
WFH1430STB	600kWh	172%	1234yf	<1	240g
WFH1430UTB	595kWh	168%	1234yf	<1	240g
BFHT1430UB	595kWh	168%	1234yf	<1	240g
BFHT1430UBOB	635kWh	157%	1234yf	<1	240g
BFT1430SKB	995kWh	104%	1234yf	<1	220g
WFH1425UTB	590kWh	160%	1234yf	<1	240g
BF1424UB	820kWh	152%	1234yf	<1	190g
BF1420UB	820kWh	144%	1234yf	<1	190g
BF1416UB	790kWh	124%	1234yf	<1	190g
BF1340UB	1290kWh	100%	1234yf	<1	290g
BFH1336SB	725kWh	151%	1234yf	<1	240g
BFH1330SB	705kWh	146%	1234yf	<1	240g
BFH1330UB	705kWh	142%	1234yf	<1	240g
BFHT1330UB	705kWh	142%	1234yf	<1	240g
BFHT1330UBOB	755kWh	132%	1234yf	<1	240g
BFT1330SKB	995kWh	104%	1234yf	<1	220g
BFH1325UB	675kWh	140%	1234yf	<1	240g
BF1324SB	840kWh	102%	1234yf	<1	200g
BF1324UB	860kWh	146%	1234yf	<1	190g
BF1320SB	784kWh	101%	1234yf	<1	200g
BF1320UB	860kWh	137%	1234yf	<1	190g
BF1316UB	860kWh	114%	1234yf	<1	190g
BF1240UB	1290kWh	100%	1234yf	<1	290g
BFH1236SB	850kWh	129%	1234yf	<1	240g
WFH1230UTB	705kWh	142%	1234yf	<1	240g
BFH1230SB	820kWh	126%	1234yf	<1	240g
BFH1230UB	830kWh	120%	1234yf	<1	240g
IFH1230UB	830kWh	120%	1234yf	<1	240g
IFH1230UTB	830kWh	120%	1234yf	<1	240g
BFHT1230UB	830kWh	120%	1234yf	<1	240g
BFHT1230UBOB	830kWh	120%	1234yf	<1	240g
BFT1230SKB	995kWh	104%	1234yf	<1	240g
WFH1225UTB	675kWh	140%	1234yf	<1	240g
BFH1225UB	795kWh	119%	1234yf	<1	240g
IFH1225UB	795kWh	119%	1234yf	<1	240g
IFH1225UTB	795kWh	119%	1234yf	<1	240g
BF1224SB	850kWh	100%	1234yf	<1	190g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BF1224UB	870kWh	144%	1234yf	<1	190g
BF1220SB	794kWh	100%	1234yf	<1	190g
BF1220UB	870kWh	136%	1234yf	<1	190g
BF1216UB	870kWh	113%	1234yf	<1	190g
BF1130UNPLB	880kWh	114%	R744	1	360g
BF1125UNPLB	885kWh	107%	R744	1	360g
BD1942TPB	915kWh	140%	1234yf	<1	160g
WD1942TPB	915kWh	140%	1234yf	<1	160g
BD1942TPRWB	915kWh	140%	1234yf	<1	160g
BD1936TPB	750kWh	153%	1234yf	<1	160g
BD1936SRWB	780kWh	142%	1234yf	<1	150g
BD1936TPRWB	750kWh	153%	1234yf	<1	160g
BD1936SB	780kWh	142%	1234yf	<1	150g
WD1936TPB	750kWh	153%	1234yf	<1	160g
BD1930TPB	715kWh	152%	1234yf	<1	150g
BD1930SB	760kWh	137%	1234yf	<1	150g
BD1930SRWB	760kWh	137%	1234yf	<1	150g
BD1930TPRWB	715kWh	152%	1234yf	<1	150g
WD1930TPB	715kWh	152%	1234yf	<1	150g
BD1920UB	820kWh	146%	1234yf	<1	130g
BD1918UB	730kWh	104%	1234yf	<1	120g
BD1842SB	915kWh	140%	1234yf	<1	160g
WD1842SB	915kWh	140%	1234yf	<1	160g
BD1836TPB	750kWh	153%	1234yf	<1	160g
BD1836SRWB	780kWh	141%	1234yf	<1	150g
BD1836TPRWB	750kWh	153%	1234yf	<1	160g
WD1836TPB	750kWh	153%	1234yf	<1	160g
BDU1830SB	440kWh	244%	R744/1234yf	1/<1	200g/250g
BDU1830UB	430kWh	239%	R744/1234yf	1/<1	200g/250g
BD1830SRWB	760kWh	137%	1234yf	<1	150g
BD1830URWB	700kWh	142%	1234yf	<1	150g
BDU1825UB	420kWh	232%	R744/1234yf	1/<1	200g/250g
BD1820UB	820kWh	145%	R744	1	160g
BD1818TB	875kWh	125%	R744	1	160g
BD1818UB	730kWh	104%	1234yf	<1	120g
BD1736TPB	750kWh	153%	R744	1	170g
BD1736SRWB	810kWh	136%	R744	1	160g
BDU1730UB	430kWh	239%	R744/1234yf	1/<1	200g/250g
BDU1730SB	440kWh	244%	R744/1234yf	1/<1	200g/250g
BD1730URWB	790kWh	126%	R744	1	160g
BD1730SRWB	795kWh	131%	R744	1	160g
BDU1725UB	420kWh	232%	R744/1234yf	1/<1	200g/250g
BD1720UB	820kWh	145%	R744	1	160g
BD1718UB	730kWh	104%	R744	1	170g
BD1718TB	875kWh	125%	R744	1	160g
BD1636SRWB	810kWh	136%	R744	1	160g
BDS1636TPB	595kWh	192%	R744/1234yf	1/<1	150g/100g
WDS1636TPB	595kWh	192%	R744/1234yf	1/<1	150g/100g
BDU1630SB	440kWh	244%	R744/1234yf	1/<1	200g/250g
BDU1630UB	430kWh	239%	R744/1234yf	1/<1	200g/250g
BD1630SRWB	795kWh	131%	R744	1	160g
BD1630URWB	790kWh	126%	R744	1	160g
BDU1625UB	420kWh	232%	R744/1234yf	1/<1	200g/250g
BD1620UB	820kWh	145%	R744	1	160g
BD1618TB	875kWh	125%	R744	1	160g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BD1618UB	730kWh	104%	R744	1	170g
BD1615TB	855kWh	121%	R744	1	160g
BDS1536TPB	625kWh	183%	R744/1234yf	1/<1	150g/100g
BD1536SRWB	810kWh	136%	R744/1234yf	1/<1	150g/100g
BDS1530SB	630kWh	165%	R744/1234yf	1/<1	150g/100g
WDS1530SB	630kWh	165%	R744/1234yf	1/<1	150g/100g
BDU1530SB	440kWh	244%	R744/1234yf	1/<1	200g/250g
BDU1530UB	430kWh	239%	R744/1234yf	1/<1	200g/250g
BD1530URWB	790kWh	126%	R744/1234yf	1/<1	150g/100g
BD1530SRWB	795kWh	131%	R744/1234yf	1/<1	150g/100g
BDS1525UB	610kWh	155%	R744/1234yf	1/<1	150g/100g
WDS1525UB	610kWh	155%	R744/1234yf	1/<1	150g/100g
BDU1525UB	420kWh	232%	R744/1234yf	1/<1	200g/250g
BD1520SB	755kWh	102%	R744	1	220g
WD1520SB	755kWh	102%	R744	1	220g
BD1520UB	815kWh	142%	R744	1	220g
BD1518UB	740kWh	102%	R744	1	200g
BD1518TB	880kWh	121%	R744	1	230g
BD1515TB	860kWh	118%	R744	1	230g
BDS1436TPB	580kWh	197%	R744/1234yf	1/<1	200g/200g
BD1436SRWB	835kWh	130%	R744	1	240g
BDU1436SB	455kWh	249%	R744/1234yf	1/<1	200g/250g
BD1430URWB	815kWh	120%	R744	1	240g
BD1430SRWB	835kWh	122%	R744	1	240g
BDU1430UB	430kWh	236%	R744/1234yf	1/<1	200g/250g
BDU1430SB	440kWh	243%	R744/1234yf	1/<1	200g/250g
BD1430UADB	815kWh	120%	R744	1	240g
BDS1425UB	550kWh	171%	R744/1234yf	1/<1	200g/200g
WDS1425UB	550kWh	171%	R744/1234yf	1/<1	200g/200g
BDU1425UB	420kWh	229%	R744/1234yf	1/<1	200g/250g
BDS1425UADB	550kWh	171%	R744/1234yf	1/<1	200g/200g
BD1418UB	740kWh	102%	R744	1	200g
BD1342SB	995kWh	128%	R744	1	240g
BD1336SB	850kWh	128%	R744	1	240g
WD1336SB	850kWh	128%	R744	1	240g
WD1336STB	850kWh	128%	R744	1	240g
BD1330SB	850kWh	120%	R744	1	240g
BD1330UB	835kWh	117%	R744	1	240g
WD1330SB	850kWh	120%	R744	1	240g
WD1330STB	850kWh	120%	R744	1	240g
BD1325UB	830kWh	112%	R744	1	240g
BD1324SB	840kWh	100%	R744	1	220g
BD1320UB	830kWh	140%	R744	1	220g
BD1318UB	750kWh	100%	R744	1	200g
BD1318TB	900kWh	119%	R744	1	230g
BD1315TB	875kWh	116%	R744	1	230g
BD1242SB	995kWh	128%	R744	1	240g
BD1236SB	850kWh	128%	R744	1	240g
BD1236SRB	850kWh	128%	R744	1	240g
WD1236SB	850kWh	128%	R744	1	240g
ID1236SB	850kWh	128%	R744	1	240g
ID1236STB	850kWh	128%	R744	1	240g
BD1230SB	850kWh	120%	R744	1	240g
BD1230UB	835kWh	117%	R744	1	240g
BD1230SRB	850kWh	120%	R744	1	240g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BD1230URB	835kWh	117%	R744	1	240g
WD1230SB	850kWh	120%	R744	1	240g
ID1230SB	850kWh	120%	R744	1	240g
ID1230STB	850kWh	120%	R744	1	240g
BD1225UB	830kWh	112%	R744	1	240g
BD1225URB	830kWh	112%	R744	1	240g
BD1224SB	845kWh	100%	R744	1	220g
ID1221LLWB	1662kWh	102%	R744	1	170g
ID1221HWB	1662kWh	102%	R744	1	170g
BD1220UB	830kWh	140%	R744	1	220g
BD1218UB	755kWh	100%	R744	1	200g
BD1218TB	900kWh	119%	R744	1	230g
BD1215TB	875kWh	116%	R744	1	230g
BN1936QPB	927kWh	131%	R600a	3	53g
WN1936QPB	927kWh	131%	R600a	3	53g
BNV1936SB	656kWh	175%	R600a	3	53g
WNV1936SB	656kWh	175%	R600a	3	53g
BNV1930SB	622kWh	174%	R600a	3	53g
BNV1930UB	616kWh	164%	R600a	3	53g
WNV1930SB	622kWh	174%	R600a	3	53g
WNV1930UB	616kWh	164%	R600a	3	53g
BNV1925UB	597kWh	160%	R600a	3	53g
WNV1925UB	597kWh	160%	R600a	3	53g
BN1924UB	901kWh	140%	R600a	3	53g
BN1918TB	950kWh	114%	R600a	3	45g
BN1915TB	931kWh	111%	R600a	3	45g
BNV1836SB	656kWh	175%	R600a	3	53g
BN1836QPB	927kWh	131%	R600a	3	53g
WNV1836SB	656kWh	175%	R600a	3	53g
WN1836QPB	927kWh	131%	R600a	3	53g
BNV1830SB	622kWh	174%	R600a	3	53g
BNV1830UB	616kWh	164%	R600a	3	53g
BNV1830TPB	616kWh	181%	R600a	3	53g
WNV1830SB	622kWh	174%	R600a	3	53g
WNV1830UB	616kWh	164%	R600a	3	53g
WNV1830TPB	616kWh	181%	R600a	3	53g
BNV1825UB	597kWh	160%	R600a	3	53g
WNV1825UB	597kWh	160%	R600a	3	53g
BN1824UB	901kWh	140%	R600a	3	53g
BN1815TB	931kWh	111%	R600a	3	45g
BNV1736SB	656kWh	175%	R600a	3	53g
BN1736QPB	927kWh	131%	R600a	3	53g
BNV1730UB	616kWh	164%	R600a	3	53g
BNV1730TPB	616kWh	181%	R600a	3	53g
BNV1730SB	622kWh	174%	R600a	3	53g
BNV1725UB	597kWh	160%	R600a	3	53g
BN1724UB	901kWh	140%	R600a	3	53g
BN1715TB	931kWh	111%	R600a	3	45g
BNV1636SB	656kWh	175%	R600a	3	53g
BN1636QPB	927kWh	131%	R600a	3	53g
WNV1636SB	656kWh	175%	R600a	3	53g
BNV1630SB	622kWh	174%	R600a	3	53g
BNV1630UB	616kWh	164%	R600a	3	53g
BNV1630TPB	616kWh	181%	R600a	3	53g
WNV1630SB	622kWh	174%	R600a	3	53g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
WNV1630UB	616kWh	164%	R600a	3	53g
WNV1630TPB	616kWh	181%	R600a	3	53g
BNV1625UB	597kWh	160%	R600a	3	53g
WNV1625UB	597kWh	160%	R600a	3	53g
BNV1536SB	656kWh	176%	R600a	3	53g
WNV1536SB	656kWh	176%	R600a	3	53g
BNV1530SB	622kWh	174%	R600a	3	53g
BNV1530UB	616kWh	164%	R600a	3	53g
BNV1530TPB	616kWh	181%	R600a	3	53g
WNV1530SB	622kWh	174%	R600a	3	53g
WNV1530UB	616kWh	164%	R600a	3	53g
WNV1530TPB	616kWh	181%	R600a	3	53g
BNV1525UB	597kWh	160%	R600a	3	53g
WNV1525UB	597kWh	160%	R600a	3	53g
BN1524TPB	835kWh	112%	R600a	3	53g
BNV1430SB	570kWh	191%	R600a	3	50g
BN1430SB	765kWh	142%	R600a	3	50g
BN1430UB	735kWh	138%	R600a	3	50g
BNV1425UB	535kWh	179%	R600a	3	50g
BN1425UB	735kWh	130%	R600a	3	50g
BN1424SB	769kWh	116%	R600a	3	50g
WN1424SB	769kWh	116%	R600a	3	50g
BN1420SB	732kWh	109%	R600a	3	50g
WN1420SB	732kWh	109%	R600a	3	50g
BN1418TB	1001kWh	109%	R600a	3	45g
BN1415TB	965kWh	107%	R600a	3	45g
BNV1336SB	730kWh	158%	R600a	3	50g
BNV1330UB	710kWh	142%	R600a	3	50g
BNV1330SB	710kWh	153%	R600a	3	50g
BNV1325UB	690kWh	139%	R600a	3	50g
BN1318TB	1041kWh	104%	R600a	3	45g
BN1315TB	1005kWh	103%	R600a	3	45g
BN1230UB	864kWh	117%	R600a	3	50g
BN1225UB	833kWh	115%	R600a	3	50g
BN1218TB	1053kWh	103%	R600a	3	45g
BN1215TB	1010kWh	102%	R600a	3	45g
BN1130UNPB	945kWh	107%	R600a	3	46g/50g
BN1125UNPB	930kWh	103%	R600a	3	46g/50g
IN1125UNPB	930kWh	103%	R600a	3	46g/50g
BN1030UNP	950kWh	106%	R600a	3	46g/50g
BN1025UNP	940kWh	102%	R600a	3	46g/50g
IN1025UNP	940kWh	102%	R600a	3	46g/50g
BN0930UP	960kWh	105%	R600a	3	47g/50g
BN0925UP	950kWh	101%	R600a	3	47g/50g
IN0925UP	950kWh	101%	R600a	3	47g/50g
IN0830SP	970kWh	112%	R600a	3	50g/50g
IN0825UP	950kWh	101%	R600a	3	50g/50g
BK1742SB	975kWh	132%	1234yf	<1	205g
BKE1736SB	580kWh	188%	1234yf	<1	285g
BK1735TPB	815kWh	146%	1234yf	<1	205g
BK1720SB	768kWh	100%	1234yf	<1	175g
BK1642SB	975kWh	132%	1234yf	<1	220g
BK1635TPB	815kWh	146%	1234yf	<1	230g
BKE1625UB	560kWh	167%	1234yf	<1	380g
BK1620SB	768kWh	100%	1234yf	<1	180g
BK1542SB	975kWh	132%	1234yf	<1	220g
BK1442SB	990kWh	130%	1234yf	<1	220g

缶・ボトル機

機種	エネルギー消費効率		冷媒		
	年間消費電力量	基準達成率	種類	GWP係数	封入量
BKE1436SB	535kWh	204%	1234yf	<1	385g
BK1342SB	990kWh	130%	1234yf	<1	220g
BK1336SB	805kWh	135%	1234yf	<1	220g
BK1330UB	795kWh	124%	1234yf	<1	220g
BK1330TPB	695kWh	152%	1234yf	<1	230g
BK1330SB	800kWh	129%	1234yf	<1	220g
BK1330TPB	695kWh	152%	1234yf	<1	230g
BK1325UB	790kWh	118%	1234yf	<1	220g
BK1324SB	840kWh	100%	1234yf	<1	190g
BK1320SB	774kWh	100%	1234yf	<1	180g
BK1242SB	990kWh	130%	1234yf	<1	220g
BK1236SB	846kWh	129%	1234yf	<1	220g
BK1230UB	830kWh	119%	1234yf	<1	210g
BK1230TPB	765kWh	138%	1234yf	<1	220g
BK1230SB	847kWh	121%	1234yf	<1	220g
BK1225UB	830kWh	112%	1234yf	<1	210g
BK1220SB	774kWh	100%	1234yf	<1	180g
KZ1630UB	795kWh	124%	1234yf	<1	210g
KZ1625UB	790kWh	118%	1234yf	<1	210g
KZ1530UB	795kWh	124%	1234yf	<1	210g
KZ1525UB	790kWh	118%	1234yf	<1	210g
KZ1430UB	795kWh	124%	1234yf	<1	210g
KZ1425UB	790kWh	118%	1234yf	<1	210g
KZ1330UB	795kWh	124%	1234yf	<1	220g
KZ1325UB	790kWh	118%	1234yf	<1	220g
KZ1230UB	830kWh	119%	1234yf	<1	210g
KZ1225UB	830kWh	112%	1234yf	<1	210g